

IMF84



2019+ JEEP JT GLADIATOR Installation Instructions Also online www.rallyarmor.com



Manufacturer warranty covers material defects on new, never installed parts. Once installed, all mud flap replacement part costs are the responsibility of the vehicle owner. Caution against blind spots during parking. Avoid curbs and excessive compression to the flaps. Check stock and aftermarket wheel/suspension clearances.



INSTALLATION QUESTION? FOR REPLACEMENT PART QUOTES, SEND FLAP RECEIPT OR PHOTO → www.rallyarmor.com/support

Recommended Tools Low-profile offset, ratcheting, flat & Phillips screwdrivers, 10mm & 11mm wrenches, pick.

ONLY install on even surface using hand tools, not powered tools. AVOID OVERTIGHTENING HARDWARE.

ABOUT OUR STANDARD IN MUD FLAPS Polyurethane is a high grade plastic that may feature minor surface layer marks. These are visual variations that don't affect flap construction or performance. Most matte away as the material ages over time.

MF84 KIT CONTENTS CONFIRM ALL PARTS AND QUANTITIES BEFORE INSTALLATION

MUD FLAP KIT PN: MF84	SEE PAGE 5 DRAWINGS	PART DESCRIPTION	QUANTITY
MF84-LF		LEFT FRONT	1
MF84-RF		RIGHT FRONT	1
MF84-LR-TOP		LEFT REAR TOP	1
MF84-RR-TOP		RIGHT REAR TOP	1
MF84-LR-BOT		LEFT REAR BOTTOM	1
MF84-RR-BOT		RIGHT REAR BOTTOM	1
BRACKET KIT PN: BMF84	SEE PG 5		
BMF54-FRT		FRONT	2
BMF84-LR PN stamped		LEFT REAR	1
BMF84-RR PN stamped		RIGHT REAR	1
HARDWARE KIT PN: HMF84	SEE PG 5		
.75SP		SPACER	6
1SS		SCREW	2
2SS		SCREW	6
HXBLT		BOLT	20
BLKNUT		NUT	20
SMWASH		WASHER	36
UCLP		CLIP	2
UNUT2		LARGE CLIP	6

2019+ JEEP JT GLADIATOR Installation Instructions Also online www.rallyarmor.com

FRONT MUD FLAP Access interior wheel well by turning steering wheel towards the installation side.

Bracket/Hardware 1 x FLAP → 1 x BMF54-FRT; 3 x .75SP; 3 x 2SS; 3 x BLKNUT; 3 x HXBLT; 6 x SMWASH; 1 x UCLP; 2 x UNUT2

FIGURE A To gain access to interior well area, remove factory fasteners 2, 3 & 6. Pull liner away.

FIGURE B Located under fender body, install UNUT2 over mounts 2 & 3. For mount 6, install UCLP behind liner.

FIGURE C Bracket **BMF54-FRT** installs against **logo-side of flap** mounts 1, 4, & 5.

Stainless steel brackets in images below for contrast only. Actual brackets are coated black.




FIGURE D/E On the **tire-side of flap**, install **SMWASH** and **HXBLT** into BMF54-FRT mounts 1, 4 & 5. Install **BLKNUT** on **logo-side of bracket/flap**, tightening just enough to adjust later.

FIGURE F/G On **tire-side of flap**, install **SMWASH & 2SS** into mounts 2, 3 & 6. Do not fully tighten. On the **bracket-side, between bracket and fender liner**, position **.75SP** against mounts 2, 3 and 6.




FIGURE H Hold flap against corner mount 2 to align bracket with edge of fender.

FIGURE I Flap should be parallel to even ground before fully tightening HXBLT, just until washer seats. Avoid overtightening.

2019+ JEEP JT GLADIATOR Installation Instructions Also online www.rallyarmor.com



REAR MUD FLAP

Bracket/Hardware 1 x FLAP → 1 x BMF84-LR/RR; 1 x 1SS; 7 x BLKNUT; 7 x HXBLT; 12 x SMWASH; 1 x UNUT2

FIGURE J Remove factory fasteners 1 & 2. Retain 2 for reinstallation later.

FIGURE K Work from rear of vehicle underbody to install UNUT2 over liner mount 1.

FIGURE L Position MF84-LR/RR-BOT over MF84-LR/RR-TOP mounting holes. To assemble top to bottom flaps, Install HXBLT and SMWASH through logo-side bottom flap. Fasten flaps on tire side with SMWASH and BLKNUT.



FIGURE M/N Angled sections of bracket facing away from you, pass HXBLT through mounting points 3, 4 and 5. Bracket with HXBLT stems facing you, align mud flap over bracket mounts 3, 4 and 5. Fasten SMWASH & BLKNUT onto HXBLT.

FIGURE O Assembled flap with BLKNUT facing tire side, slide bracket between liner and bumper.

2019+ JEEP JT GLADIATOR Installation Instructions Also online www.rallyarmor.com





FIGURE P Use factory fastener 2 to secure bracket mount 2.

FIGURE Q Install SMWASH & 1SS onto bracket mount 6.


FIGURE R Ensure flap is parallel to even ground before tightening washers just until flush against flap.



IMF84



2019+ JEEP JT GLADIATOR Installation Instructions Also online www.rallyarmor.com



**ALWAYS TEST COMPATIBILITY
WITH YOUR SPECIFIC WHEEL,
TIRE AND SUSPENSION
COMBINATION**



**ALWAYS USE
CAUTION DURING
PARKING/REVERSAL
SCENARIOS**



**CLEANING INSTRUCTIONS:
USE WATER AND SOFT CLOTH
TO CLEAN FLAPS. AVOID
SOLVENT BASED CLEANERS**

